



Français

1 of 1

Images Description and Claims (47 Kb)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION  
TREATY (PCT)

(11) WO 03/043061

(13) A1

(21) PCT/US02/36557

(22) 13 November 2002 (13.11.2002)

(25) English

(26) English

(30) 60/338,034

13 November 2001  
(13.11.2001)

US

(43) 22 May 2003 (22.05.2003)

(51)<sup>7</sup> H01L 21/00, H01J 37/32

(54) APPARATUS AND METHOD FOR IMPROVING ETCH RATE UNIFORMITY

(71) LAM RESEARCH [US/US]; 4650 Cushing Parkway, Fremont, CA 94538-6470 (US).

(72) DHINSA, Rajinder; 3670 Rollingside Drive, San Jose, CA 95148 (US).

KADKHODAYAN, Bobby; 4328 Howe Street #7, Oakland, CA 94611 (US).

(74) RITCHIE, David, B., et al; Thelen Reid & Priest LLP, P.O. Box 640640, San Jose, CA 95110 (US).


(81) AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW

(84) ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

#### Published

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(57) An etching apparatus has a chamber enclosing a first electrode, a second electrode, confinement rings, a focus ring, and a shield. The first electrode is coupled to a source of a fixed potential. The second electrode is coupled to a dual frequency RF power source. The confinement rings are disposed between the first electrode and the second electrode. The chamber is formed of an electrically conductive material coupled to the source. The focus ring substantially encircles the second electrode and electrically insulates the second electrode. The shield substantially encircles the focus ring. The distance between an edge of the second electrode and an edge of the shield is at least less than the distance between the



BEST AVAILABLE COPY

edge of the second electrode and an edge of the first electrode. The shield is formed of an electrically conductive material coupled to the source of fixed potential.

---



Français   
1 of 1

**BEST AVAILABLE COPY**